

Outdoor Company Switch

100A., 120/208V., Posi-Lok™ and Connection Chamber

IMAGE
NOT
AVAILABLE

- Electric power distribution center for theatre, convention centers, arenas, schools, churches, and events centers
- 200A. Posi-Lok™ receptacle panel
- Sequential interlocking type of receptacle panel
- 100A. Main breaker rated 65K AIC
- Connection chamber for bare-end cables. Door is electrically interlocked with main breaker shunt trip
- Outdoor rated Type 3R enclosure
- Options:
 - ✧ Parallel sets of receptacles
 - ✧ Isolated Ground
 - ✧ 1Ø - 120V., 120/240V.,
 - ✧ 3Ø - 277/480V., 208V., 480V.
 - ✧ Digital Meter
 - ✧ Custom color finish
 - ✧ Recessed or Pad mounting
 - ✧ Type 4 or 4X enclosure

Catalog Number:	CSC-1010-PSP-3R
Product Type:	Company Switch with Posi-Lok™ receptacle panel and connection chamber
Main Enclosure:	TYPE 3R, Galvanized Steel, ANSI 61 Gray powder-coat finish, wall mounting brackets, door for portable cable on bottom of enclosure
Dimensions:	40"H. x 24"W. x 10" D.
Rating:	100A., 120/208V., 3Ø, 4W+G
Circuit Breakers:	Molded-case, UL489, 65K AIC @ 240V., (1) 100A., 3-pole
Receptacles:	200A. Posi-Lok™ receptacle panel
Busbar Output:	(5) dual rated mechanical lugs on copper bus accessible in connection chamber
Monitoring:	LED Indicator lights to indicate presence of phase voltage.
Labelling:	Laser engraved cam identifiers and panel rating. Cable connection warning label per NEC Art 520.
Listing:	UL Listed