

# Outdoor Company Switch

400A., 120/208V., Posi-Lok™ and Connection Chamber

IMAGE  
NOT  
AVAILABLE

- Electric power distribution center for theatre, convention centers, arenas, schools, churches, and events centers
- 400A. Posi-Lok™ receptacle panel
- Sequential interlocking type of receptacle panel
- 400A. Main breaker rated 65K AIC
- Connection chamber for bare-end cables. Door is electrically interlocked with main breaker shunt trip
- Outdoor rated Type 3R enclosure
- Options:
  - ✧ Parallel sets of receptacles
  - ✧ Isolated Ground
  - ✧ 1Ø - 120V., 120/240V.,
  - ✧ 3Ø - 277/480V., 208V., 480V.
  - ✧ Digital Meter
  - ✧ Custom color finish
  - ✧ Recessed or Pad mounting
  - ✧ Type 4 or 4X enclosure

- Catalog Number:** CSC-4020-PSP-3R
- Product Type:** Company Switch with Posi-Lok™ receptacle panel and connection chamber
- Main Enclosure:** TYPE 3R, Galvanized Steel, ANSI 61 Gray powder-coat finish, wall mounting brackets, door for portable cable on bottom of enclosure
- Dimensions:** 42"H. x 24"W. x 12" D.
- Rating:** 400A., 120/208V., 3Ø, 4W+G
- Circuit Breakers:** Molded-case, UL489, 65K AIC @ 240V., (1) 400A., 3-pole
- Receptacles:** 400A. Posi-Lok™ receptacle panel
- Busbar Output:** (5) dual rated mechanical lugs on copper bus accessible in connection chamber
- Monitoring:** LED Indicator lights to indicate presence of phase voltage.
- Labelling:** Laser engraved cam identifiers and panel rating. Cable connection warning label per NEC Art 520.
- Listing:** UL Listed