

Outdoor Basic Company Switch Type 3R with Series 16 Cam Receptacles

Electric Power Distribution Center For Theatres, Convention Centers, Arenas, Schools, Churches, And Events Centers

Part Number : CSC-1010-CL-3R

Dimensions : 24" x 20" x 8"

Weight : 68 lbs.



- Type 3R Powder Coated ANSI 61 Gray Enclosure
- Hinged Main Access Door Provided with a Latch Able To Accept a Padlock.
- Internally Locking Portable Cable Access Door in the Bottom of the Enclosure
- 100A, 100% Rated, 65k AIC @ 240V Molded Case Main Circuit Breaker
- (5) Color Coded Standard Series 16 Cam Receptacles
- (5) Color Coded Series 16 Snapback Protective Covers
- (1) Indicator Light per Line Receptacle
- Laser Engraved and Silkscreen Labels
- UL Listed



Enclosure Options:

- Type 1
 - Galvanized Steel
 - Stainless Steel
 - Aluminum
- Type 4X
 - Stainless Steel
 - Aluminum

Device Type Options:

- Series 16 Cam-Lok
- Series 16 SafeCam
- E0400 Posi-Lok (400A)
- E0200 Posi-Lok (200A)
- IEC 309 Pin & Sleeve (100A Max.)

Device Options:

- Dual Neutral
- Reverse Neutral
- Reverse Ground
- Isolated Ground
- Dual Ground
 - (1) isolated
 - (1) frame
- Dual Receptacles

Mounting Option:

- Surface (Wall)
- Recesses (Flush)
- Pad Mount (Freestanding)

Unit Options:

- Digital Ammeter
- Digital Voltage Meter
- Digital Multimeter (Amp & Volt)
- Fire Alarm Input
- Receptacle Behind a Door
- Bottom Feed
- Parallel Feed
- Front Facing Receptacles
- Kirk Key Lock on Circuit Breaker
- Circuit Breaker with Remote Operator
- Circuit Breaker and Receptacles in Separate Enclosures

Voltage Options:

- 120/208V (3Ø 4W + G)
- 120/240V (1Ø, 3W + G)
- 277/480V (3Ø, 4W + G)
- 347/600V (3Ø, 4W + G)
- 208V (3Ø, 3W + G)
- 480V (3Ø, 3W + G)
- 600V (3Ø, 3W + G)